

### **Amendments to the Claims**

This listing of claims will replace all prior versions and listings of claims in the subject application.

### **Listing of Claims:**

1-8 (Cancelled)

9. (Currently Amended) An actuator comprising:

a base plate;

a lever pivotally mounted to said base plate by a pin, said lever comprising a lever roller, and said lever being pivotable between a first position and a second position;

a stationary roller disposed on said base plate;

a solenoid mounted to said base plate and comprising a plunger moveable between an extended position and a retracted position, wherein said plunger is ~~disposed~~ compressed between said lever roller and said stationary roller in said extended position of said plunger and in said first position of said lever, preventing said lever from pivoting to said second position.

10. (Original) The actuator according to claim 9 further comprising a torsion spring biasing said lever toward said first position.

11. (Cancelled)

12. (Original) The actuator according to claim 9 further comprising a mechanical switch that is closed when said lever is in said second position.

13. (Original) The actuator according to claim 9 wherein said plunger comprises a wedge-shaped portion.

14-22. (Cancelled)

23. (Previously Presented) An actuator comprising:

a base plate;

a latching lever pivotally mounted to said base plate by a pin and pivotable between at least a first position and a second position, said lever comprising a lever bearing surface;

a stationary bearing surface; and

a solenoid mounted to said base plate and comprising a plunger moveable between an extended position and a retracted position, wherein in said first position of said lever and in said extended position of said plunger, said plunger is compressed between said lever bearing surface and said stationary bearing surface blocking said lever from pivoting to said second position, and in said retracted position of said plunger said lever is not blocked from pivoting between said first position and said second position.

24. (Previously Presented) The actuator of claim 23, wherein at least one of said lever bearing surface and said stationary bearing surface comprises a roller.

25. (Previously Presented) The actuator of claim 23, wherein said lever is biased toward one of said first position and second position.

26. (Previously Presented) The actuator of claim 25, wherein said lever is biased toward said first position by a torsion spring.

27. (Previously Presented) The actuator of claim 23, wherein said plunger is biased toward one of said extended position and said retracted position when said solenoid is in an un-energized state.

28. (Previously Presented) The actuator of claim 23, further comprising a mechanical switch that is closed when said lever is in one of said first position and said second position.

29. (Previously Presented) The actuator of claim 23, wherein said plunger comprises a wedge-shaped portion.